Detalles de producto **HTI 400W/24**



Nombre: HTI 400W/24
Nro de Producto: 4050300228327
Cantidad solicitada: Estuche de cartón (FS) contiene 1 Unidad (ST)

Aplicaciones	
Enfriamiento	Refrigeración forzada [1)]
Posición de funcionamiento	p 20

Descripción general	
Construcción / Modelo	Con cable
Casquillo (denominación estándar)	FaXP2.5-2x65
Conector: presencia	J

Datos logísticos	
Peso del producto	115 g

Datos técnicos eléctricos	
Tensión de encendido	4.5/20 kVp
Tensión de construcción	55 V
Tensión de funcionamiento	55 V
Corriente de construcción	7.3 A
Lamp current	7.3 A
Potencia de construcción	400 W

Geometrías	
Diámetro	67.0 mm
Distancia entre electrodos en frío	4.2 mm
Longitud	73 mm
Longitud del cable en mm	9999,90 mm

Duración	
Duración	250 h

Datos técnicos de iluminación	
Temperatura de color	5600 K
Índice de reproducción cromática Ra	85
Longitud focal	24.0 mm

Temperaturas	
Temperatura máx. admisible en la tempera	350 °C [2)]

Opciones de embalaje

Product code	Tipo de embalaje y contenido	Dimensión en a x a x l	Peso bruto	Volumen
4050300228327	Estuche de cartón contiene 1 Unidad	87,000 mm x 87,000 mm x 103,000 mm	153,000 g (0,000 g)	0,780 dm3
4050300228334	Embalaje de envío contiene 2 Unidad	115,000 mm x 123,000 mm x 186,000 mm	352,000 g (0,000 g)	2,160 dm3

Subject to change without notice. Errors and omission excepted.
© 2010 OSRAM GmbH



Detalles de producto **HTI 400W/24**

Safety

Because of their high luminance, UV radiation and high internal pressure during operation, HTI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

HTI reflector lamps are short-arc lamps and have dichroic focusing reflectors. They are highly efficient lighting systems for injecting light into light guides. They are used in medical endoscopy, industrial boroscopy and light guide systems in the entertainment sector.

1) fan

2) measured at Molybdenium foil / Pinch Seal region (eXtreme Seal Technology)

Subject to change without notice. Errors and omission excepted.
© 2010 OSRAM GmbH