



Detalles de producto

EMH 150W/SE/70

Nombre: EMH 150W/SE/70
Nro de Producto: 4008321345004
Cantidad solicitada: Estuche de cartón (FS) contiene 1 Unidad (ST)

Aplicaciones	
Posición de funcionamiento	Universal ¹⁾

Categorizations	
NAED	55086

Descripción general	
Casquillo (denominación estándar)	GY9.5
Lamp reference type	HTI 150W

Datos logísticos	
Peso del producto	0 g

Datos técnicos eléctricos	
Tensión de construcción	95 V
Potencia de la lámpara	150 W
Tensión de funcionamiento	90 V
Corriente de construcción	1.6 A
Lamp current	1.8 A
Potencia de construcción	150 W

Geometrías	
Diámetro	13 mm
Longitud con casquillo pero sin pitones/	46 mm
Longitud del filamento	5.00 mm
Distancia al centro del cuerpo luminoso	30 mm
Longitud	46 mm

Duración	
Duración	500 h

Datos técnicos de iluminación	
Flujo luminoso en lm	8000 lm
Temperatura de color	7000 K
Luminancia	5000 cd/cm ²
Índice de reproducción cromática Ra	70

Opciones de embalaje				
Product code	Tipo de embalaje y contenido	Dimensión en a x a x l	Peso bruto	Volumen
4008321345004	Estuche de cartón contiene 1 Unidad	64,000 mm x 29,000 mm x 94,000 mm	35,300 g (0,000 g)	0,174 dm ³
4008321345011	Embalaje de envío contiene 10 Unidad	160,000 mm x 150,000 mm x 203,000 mm	529,000 g (0,000 g)	4,872 dm ³





Detalles de producto

EMH 150W/SE/70

EMH lamps are short arc lamps in which the discharge arc burns in an atmosphere of mercury vapor and various halide additives at high pressure (no overpressure with a cold lamp).

The most important properties and benefits

- EMH provides effective high-quality light at an attractive price (EMH = Economy Metal Halide)
- EMH lamps are economical versions of the most popular metal halide lamps. They are powerful and durable. EMH lamps also reflect the high quality for which the name of OSRAM is widely famous
- Thanks to their excellent price/performance ratio EMH lamps are ideal for use in clubs, shops and small stages
- EMH lamps are available in different wattages and color temperatures, in single-ended and double-ended versions

Safety

Because of their high luminance, UV radiation and high internal pressure during operation EMH lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Literature

Further technical information on EMH lamps and information for manufacturers of operating equipment can be requested directly from OSRAM.

¹⁾ Arc position horizontal