




GE
Lighting



992
kWh/1000h

D
energy class

21
lumens/watt

Single Ended Halogen

T19 FWR 230-240V

88457

Product information

Quartzline® lamps designed for optimum performance in today's precision range of stage, studio and architectural luminaires. Full range up to 24,000 W
-Range of bases to meet the needs of OEMs -
Chromised seal protection up to 500° C.

Application areas



Film and Broadcast



Theatre



Product data

Cap/Base	GX9.5
Bulb Shape	Tubular
Bulb Diameter [mm]	35
Maximum Overall Length [mm]	105
Light Center Length [mm]	55
Net weight per piece [g]	45
Gross weight per piece [g]	150
Brand	General Electric (GE)

Performance data

Colour Rendering Index (CRI) [Ra]	100
Nominal correlated colour temperature (CCT) [K]	3050
Nominal lumens [lm]	21000
Energy efficiency class (EEC)	D
Rated Life [h]	750
Weighted energy consumption [kWh/1000h]	991.38

Electrical data

Nominal power [W]	1000
Nominal lamp voltage [V]	240
Coil type	C-13D
Dimming Capability	Yes
Ballast Required	No

Logistic data

DUN Code	10043168884577
EAN Code	0043168884570
Pack Quantity	12
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	144 EUR. 180 UK
Layer quantity EUR	144
Layer quantity UK	180
Pallet quantity EUR (PC)	1152
Pallet quantity UK (PC)	1440
Outer case size	190 x 350 x 126 (mm)
Product status	Available

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Entertainment Solution Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

[Certificate for the Quality Management System of GE Lighting EMEA \(PDF\)](#)

[Certificate for the Environmental Management System of GE Lighting EMEA \(PDF\)](#)

Disclaimer

Special Purpose Lamp, Not suited for household illumination