











Single Ended Halogen **CP29 230V** 

88875

# **Product information**

Quartzline® lamps designed for optimum performance in today's precision range of stage, studio and architectural luminaires. Full range up to 24,000 W -Range of bases to meet the needs of OEMs -Chromised seal protection up to 500° C.

#### **Application areas**



Film and Broadcast



(F) Theatre









## **Product data**

Cap/Base	G38
Bulb Shape	Globe
Bulb Diameter [mm]	65
Maximum Overall Length [mm]	280
Light Center Length [mm]	165
Net weight per piece [g]	350
Gross weight per piece [g]	600
Brand	General Electric (GE)

### Performance data

Colour Rendering Index (CRI) [Ra]	100
Nominal correlated colour temperature (CCT) [K]	3200
Nominal lumens [lm]	135000
Energy efficiency class (EEC)	С
Rated Life [h]	375
Weighted energy consumption [kWh/1000h]	5040

## **Electrical data**

Nominal power [W]	5000
Nominal lamp voltage [V]	230
Coil type	C-13
Dimming Capability	Yes
Ballast Required	No





### Logistic data

DUN Code	10043168888759
EAN Code	0043168888752
Pack Quantity	1
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	18 EUR. 23 UK
Layer quantity EUR	18
Layer quantity UK	23
Pallet quantity EUR (PC)	126
Pallet quantity UK (PC)	161
Outer case size	340 x 135 x 140 (mm)
Product status	Available

#### **Downloads & Links**

Go to the catalog site (HTTP)

**Entertainment Solution Spectrum Catalogue (PDF)** 

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

#### Disclaimer

Special Purpose Lamp, Not suited for household illumination