

Part number


# PEW 6365 PI



## Brief description:

bulkhead mounting housings, sockets, 3 poles + N + PE, 63 (A.C.), 346 ÷ 415V, 6 red, inclined, IP67

### Product description

<b>Model</b>	sockets
<b>Version</b>	PLUSO, plugs and socket-outlets
<b>Series</b>	PEW...PI
<b>Product type</b>	flush-mounting
<b>Style</b>	inclined
<b>Family</b>	plugs and socket-outlets
<b>N. of poles</b>	3 poles + N + 
<b>Clock position</b>	6

### Technical data

<b>Current</b>	63 A
<b>Voltage</b>	200/346 ÷ 240/415 V
<b>Frequency</b>	50 and 60 Hz.
<b>Operating temperature range (min, max)</b>	-40°C ... +125°C
<b>Material</b>	thermoplastic
<b>IP degree of protection</b>	IP67

### Further technical details

<b>Weight</b>	724,00 g
---------------	----------

### Approvals / Standards

<b>Reference standard</b>	EN 60309-1 and -2
---------------------------	-------------------

<b>Quality mark</b>	
---------------------	---

### General ordering information

<b>EAN13 code</b>	8015747077590
-------------------	---------------

### Packaging Information

<b>Packaging length</b>	290,00 mm
<b>Packaging height</b>	140,00 mm
<b>Packaging width</b>	215,00 mm
<b>Packaging weight</b>	3,11 kg
<b>Packaging volume</b>	8,73 dm <sup>3</sup>
<b>Packaging description</b>	Carton box
<b>Packaging quantity</b>	4 Pcs
<b>Packaging EAN code</b>	8015747077606

Part number

# PEW 6365 PI



Catalogue drawings

( 63 /125A) PEW ... PI



PEW ... PI	A	B	C	D	E	F	G	H	I	X	Y
<b>63A</b> 2P+⊕	100	107	124	84	55	107	82	45	94	77	85
3P+⊕	100	107	124	84	55	107	82	45	94	77	85
3P+N+⊕	100	107	124	84	55	107	82	45	94	77	85
<b>125A</b> 2P+⊕	130	130	143	94	87	119	102	56	112	104	104
3P+⊕	130	130	143	94	87	119	102	56	112	104	104
3P+N+⊕	130	130	143	94	87	119	102	56	112	104	104

## Notes

- Compliant with EN 60309-1 and -2
- Enclosure, insert and spring lid in insulating, thermoplastic, self-extinguishing material
- RAL 7035 grey enclosure, spring lid colour coded according to the operating voltage
- Flange with anti-ageing gasket
- PE...PI types (IP44), spring lid
- PEW...PI types (IP67), spring lid with locking ring and gasket
- Terminals with retained screws
- 63A, 125A: with pilot contact
- Nickel-plated contacts, available on request for 16A and 32A (standard on 63A and 125A). For the code of products with nickel-plated contacts (socket holes, plug pins), add "N" to the pre-code of the corresponding standard product code; for example: PE becomes PEN and PEW becomes PEWN.
- IP44 and IP67 degrees of protection (EN 60529)