











Single Ended Halogen CP43 FTL 230-240V

88533

Product information

Quartzline® lamps designed for optimum performance in today's precision range of stage, studio and architectural luminaires. Full range up to 24,000 W -Range of bases to meet the needs of OEMs -Chromised seal protection up to 500° C.

Application areas



Film and Broadcast



(F) Theatre









Product data

Product Code	88533
Bulb Shape	Tubular
Bulb Diameter [mm]	26.5
Maximum Overall Length [mm]	145
Light Center Length [mm]	70
Net weight per piece [g]	80
Gross weight per piece [g]	165
Brand	General Electric (GE)
Cap/Base	GY16

Performance data

Weighted energy consumption [kWh/1000h]	2024.69
Energy efficiency class (EEC)	С
Rated Life [h]	400
Nominal correlated colour temperature (CCT) [K]]	3200
Nominal lumens [lm]	54000
Colour Rendering Index (CRI) [Ra]	100

Electrical data

Coil type	C-13D
Dimming Capability	Yes
Ballast Required	No
Nominal power [W]	2000
Nominal lamp voltage [V]	240





Logistic data

DUN Code	10043168885338
EAN Code	0043168885331
Pack Quantity	12
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	144 EUR, 180 UK
Layer quantity EUR	144
Layer quantity UK	180
Pallet quantity EUR (PC)	1152
Pallet quantity UK (PC)	1440
Outer case size	350 x 190 x 120 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination